



**Frese ad inserti per spianatura a 45° con attacco a manicotto**

Fresa ad inserti per spianatura a 45° a passo differenziato, **con passaggio interno del lubrorefrigerante**, dalla geometria negativa utilizzabile su macchine con potenze medio alte.



Codice	€	Dimensioni					
		D (mm)	De (mm)	d (H7) (mm)	H (mm)	p (mm)	Z
A580130050	◆	50	63	22	40	6	4
A580130063	◆	63	76	22	40	6	6
A580130080	◆	80	93	27	50	6	7
A580130100	◆	100	113	32	50	6	8
A580130125	◆	125	138	40	63	6	10
A580130160	◆	160	173	40	63	6	12
A580130200	◇	200	213	60	63	6	14
A580130250	◇	250	263	60	63	6	16
A580130500	◆	50	63	22	40	6	6
A580130630	◆	63	76	22	40	6	8
A580130800	◆	80	93	27	50	6	10
A580131000	◆	100	113	32	50	6	12
A580131125	◆	125	138	40	63	6	16
A580131160	◆	160	173	40	63	6	20

Ricambi		
Inserto	Vite	Giravite
SNEX-SNKX-SNMX 1206 SNMU 1206 ONMU 1205	A910350045	A559250100

Ricambi: vedi pag. 492/493/494.

Codice	€	Assortimento di frese	
		Composto da	
A580139000	◆	1 fresa cod. A580130050 + 10 inserti SNMU 1206 ANER cod. A932051550 + 10 inserti ONMU 1205 ANN MB cod. A932100550	
A580139005	◆	1 fresa cod. A580130063 + 10 inserti SNMU 1206 ANER cod. A932051550 + 10 inserti ONMU 1205 ANN MB cod. A932100550	
A580139010	◆	1 fresa cod. A580130080 + 10 inserti SNMU 1206 ANER cod. A932051550 + 10 inserti ONMU 1205 ANN MB cod. A932100550	

Codice	€	Pz.	Foto	Denominazione	Figura	Dimensioni (mm)					Classi metallo duro									
						l	d	s	d1	r	Non rivestiti		Rivestiti							Cermet
											NK 15	NP 25	RP 200	RP 300	RK 300	RK 400	KTP 230	TIN	TIALN	CX 55
A930720505	◆	10		SNEX 1206 ANN-MA ALU		12,7	2,5	6,4	5,2	2,36	●									
A930820555	◆	10		SNKX 1206 ANN-MM1		12,7	2,5	6,4	5,2	2,36						●				
A930830540	◆	10		SNMX 1206 ANN-MB1		12,7	2,5	6,4	5,2	2,36			●							
A930831045	◆	10		SNMX 1206 ANN-MB1		12,7	2,5	6,4	5,2	2,36				●						
A930831550	◆	10		SNMX 1206 ANN-MB1		12,7	2,5	6,4	5,2	2,36					●					
A932050540	◆	10		SNMU 1206 ANER		12,7	2,5	6,9	5,4	2,36			●							
A932051045	◆	10		SNMU 1206 ANER		12,7	2,5	6,9	5,4	2,36				●						
A932051550	◆	10		SNMU 1206 ANER		12,7	2,5	6,9	5,4	2,36					●					
A932100540	◆	10		ONMU 1205 ANN-MB		12,7	5,2	6	6	0,5			●							
A932100545	◆	10		ONMU 1205 ANN-MB		12,7	5,2	6	6	0,5				●						
A932100550	◆	10		ONMU 1205 ANN-MB		12,7	5,2	6	6	0,5					●					

Tabella materiali e parametri di utilizzo consigliati vedi pag. 307/308/309/310/311/312/313/314/315.